

09/745563
ASW
3-8-0112/21/00
1c618 U.S. PTOGUIDE APPARATUS FOR GUIDING SHEETS, AND METHOD OF OPERATING AGUIDE APPARATUSBackground of the Invention:Field of the Invention:

The invention relates to a guide apparatus for guiding sheets to a sheet-processing machine.

10

Sheet-processing machines are known, such as printing machines in which an underlapped stream of sheets is fed over a feed table to an acceleration system belonging to the machine. In this case, a sheet is drawn off the feed table and

15

accelerated, while the sheet located underneath is being aligned and quietened at front lays or front top lays in the sheet transport and lateral directions. The sheet can be

20

influenced so severely by the sheet running out that, for example, it shoots over the front lays or front top lays and runs with it into the machine. In order to separate this "imbricated formation", that is to say the sheets overlapping each other, a guide apparatus is used such as is disclosed by German Patent DE 296 15 996 U1, for example. The guide apparatus disposed above the feed table deflects the outgoing

25 sheet in such a way that a large separating angle is produced between the feed table and the sheet running out over the

front top lay, so that the sheet located underneath is guided reliably under the top lays.

Depending on the printing-material thickness, the printing-
5 material stiffness, the sheet format and the machine speed,
the distance between the guide apparatus and the feed table
and, in the paper running direction, the front lays or front
top lays can be adjusted. The guide apparatus has a stable
shaft which is continuous over the feed table and impairs the
10 accessibility of the machine operator to the front lays, for
example to remove a misfed sheet or to set the print-free
margin. In addition, it has proven to be disadvantageous that
it is not possible to ensure the reliable entry of the first
sheet of a stream of sheets, in particular in the case of
15 thick printing materials which are very wavy at the sheet
leading edge, in all cases to the guide apparatus or,
respectively, to the front lays/front top lays.

Summary of the Invention:

20 It is accordingly an object of the invention to provide a
guide apparatus for guiding sheets, and a method of operating
a guide apparatus that overcome the above-mentioned
disadvantages of the prior art devices and methods of this
general type.

With the foregoing and other objects in view there is provided, in accordance with the invention, a guide apparatus for guiding sheets to a sheet-processing machine, including a printing machine. The guide apparatus is formed of a guide
5 element to be disposed above a feed table, and a height-adjusting device connected to the guide element for adjusting a distance between the guide element and the feed table. The height-adjusting device has a first drive and a second drive which can be actuated independently of each other.

10

The solution contains at least one guide element which is disposed above a feed table and whose distance from the feed table can be set with the aid of a height-adjusting device.

The guide apparatus is distinguished by the fact that the
15 height-adjusting device has a first drive and a second drive, which can be actuated independently of each other. The first drive is used to open the guide apparatus, that is to say to

enlarge its distance from the feed table in such a way that the accessibility for a machine operator is improved. The
20 advantage here is that a misfed sheet can readily be removed and, for example, the adjustment of at least one front lay,

which is used to align the leading edge of the sheet transversely with respect to the sheet transport direction, can readily be performed. The second drive is used for the
25 exact setting of the distance of the guide apparatus or of the guide element in relation to the feed table, so that low-

marking onward transport of the sheets can be ensured. The height adjustment of the guide element is preferably carried out steplessly.

5 In a preferred embodiment of the invention, the first and second drives can be coupled to each other, that is to say, one of the two drives acts on the other drive during the height adjustment of the guide element. The two drives can exhibit some interaction when actuated by one drive, although
10 they are driven independently of each other. In other words, the drives which respectively have at least one moving actuating device for displacing the guide element act together in such a way that, during the displacement of the actuating device of the one drive, the actuating device of the other
15 drive is also displaced by the actuating device of the one drive.

In an advantageous exemplary embodiment of the guide apparatus, the first drive is formed by a piston/cylinder
20 unit, which in a preferred embodiment can be actuated pneumatically. Using the piston/cylinder unit, the guide element can be displaced in a straightforward way into at least two positions at a distance from the feed table. Of course, the guide element can also be displaced by the
25 piston/cylinder unit into more than two defined positions at a

distance above the feed table, for example by a motor-adjustable stop.

A further exemplary embodiment of the guide apparatus is distinguished by the fact that the second drive has an actuating motor with the aid of which a stepless, preferably precise change in the distance of the guide element with respect to the feed table can be implemented. In a preferred embodiment, with the aid of the actuating motor, an actuating element interacting with the second end of a piston rod of the piston/cylinder unit that forms the first drive can be displaced in the direction of the longitudinal mid-axis of the piston rod. The change in the vertical distance of the guide element in relation to the feed table is carried out, when the second drive is activated, in such a way that both the actuating element of the second drive and the actuating element of the first drive, namely the piston rod, are displaced, without the first drive being activated for this purpose. On the basis of this coupling of the two drives to each other, a modular configuration of the height-adjusting device can be implemented.

In a further exemplary embodiment of the guide apparatus, a foreign-body protective apparatus is provided which, in order to enlarge the distance between the guide element and the feed table, activates at least one of the drives of the height-

adjusting device. The first drive, which can open the guide apparatus, is preferably activated, so that damage to the guide apparatus or to the front lay caused by a foreign body can reliably be prevented. When the guide apparatus is

5 opened, the machine is preferably switched off, and this can already be done before the guide apparatus has been opened completely. On the basis of this configuration, a machine guard is also provided at the same time by the foreign-body protective apparatus.

10 In a preferred embodiment, the foreign-body protective apparatus is configured in such a way that when a force is exceeded which is directed away from the feed table in the vertical direction and acts on a guide which bears the guide
15 element, the drive is activated. This is carried out, for example, when forces greater than 50 N act on the foreign-body protective apparatus or on the guide apparatus.

According to a development of the invention, provision is made
20 for the guide element to be disposed on a cross member which is connected to the guide and can be pivoted about an axis running transversely with respect to the sheet transport direction. The guide element, which is formed for example by a freely rotatable separating roller, is moved in the
25 direction of the front lay or away from the front lay when the crossmember is pivoted. The distance between the guide

element and the front lay can therefore be set. The action of pivoting the crossmember can be carried out by at least one lifting device fitted to the guide, such as a piston/cylinder unit, so that the distance between the guide element and the front lay can be set automatically. On the basis of the ability of the guide element to be displaced in the sheet transport direction, the guide element can advantageously be displaced very close to the at least one front lay or front top lay as a first sheet in an imbricated formation, that is to say a stream of sheets, runs in. As a result, particularly reliable feeding or threading of the stream of sheets can be implemented. For the following sheets, the guide element is displaced counter to the sheet transport direction, so that the separating angle for stiff printing materials can be reduced, in order to prevent marking.

In accordance with an added feature of the invention, a guide can be displaced in a vertical direction by the height adjusting device and has racks, including a first rack and a second rack, disposed on a drive and operator side of the sheet-processing machine and on which the cross-member is to be pivotably mounted.

In accordance with an additional feature of the invention, a rotatable geared shaft is disposed in a fixed location, and the racks mesh with the rotatable geared shaft.

In accordance with another feature of the invention, a third rack is coupled to the guide and connected to the piston rod.

- 5 In accordance with a further feature of the invention, the guide element is clamped to the cross-member, and a distance between the guide element and a longitudinal mid-axis of the cross-member can be set.

- 10 In accordance with another added feature of the invention, the guide element is one of a number of guide elements disposed at a distance from one another and fixed to the cross-member, and it being possible to set a distance from the longitudinal mid-axis of the cross-member individually.

- 15 In accordance with another additional feature of the invention, the guide element is a separating roller having a convex configuration.

- 20 In accordance with a further added feature of the invention, the cross-member is a front lay guard.

- In accordance with a further additional feature of the invention, a vertically adjustable brush is disposed on the
25 front lay guard.

The guide apparatus has at least one guide element which - as viewed in the sheet transport direction - is disposed upstream of at least one front lay. Sheets can be fed to the guide apparatus in underlapped form, that is to say the trailing edge of a preceding sheet overlaps the leading edge of a following sheet. The method is distinguished by the fact that, when the first sheet of a stream of sheets runs in, the guide element - as viewed in the sheet transport direction - is disposed at a short distance from the front lay and that, for the following sheets, the distance between the guide element and the front lay is enlarged. As a result, the secure transportation and feeding into the machine of the first sheet, whose leading edge may be very wavy and can stick upward, is ensured. After the first sheet has passed the guide apparatus, the guide element is displaced counter to the sheet transport direction to such an extent that the separating angle for stiff printing materials can be reduced, in order to prevent marking, and marking-free transportation can be ensured.

In accordance with another feature of the invention, there are the steps of automatically changing the distance between the guide element and the feed table and the distance between the guide element and the front lay.

In accordance with a concomitant feature of the invention, there is the step of setting the distance between the front lay and the guide element steplessly.

- 5 Other features which are considered as characteristic for the invention are set forth in the appended claims.

Although the invention is illustrated and described herein as embodied in a guide apparatus for guiding sheets, and a method
10 of operating a guide apparatus, it is nevertheless not intended to be limited to the details shown, since various modifications and structural changes may be made therein without departing from the spirit of the invention and within the scope and range of equivalents of the claims.

15 The construction and method of operation of the invention, however, together with additional objects and advantages thereof will be best understood from the following description of specific embodiments when read in connection with the
20 accompanying drawings.

Brief Description of the Drawings:

Fig. 1 is a diagrammatic, side-elevational view and sectional view, in parts, of a detail of a first exemplary embodiment of
25 a guide apparatus according to the invention;

Fig. 2 is a front-elevational view of a detail of the guide apparatus illustrated in Fig. 1, as viewed in a sheet transport direction;

5 Figs. 3 and 4 are side views of a further detail of the guide apparatus shown in Figs. 1 and 2; and

Fig. 5 is a side view and partially a sectional view of a detail of an exemplary embodiment of a height-adjusting device
10 for the guide apparatus.

Description of the Preferred Embodiments:

In all the figures of the drawing, sub-features and integral parts that correspond to one another bear the same reference
15 symbol in each case. Referring now to the figures of the drawing in detail and first, particularly, to Fig. 1 thereof, there is shown a guide apparatus 1 which can be used generally for guiding sheets, such as paper or board sheets, to a machine, for example a printing machine.

20

Fig. 1 shows a side view of a part of the machine for processing sheets in a feeder area in which a feed table 3 is disposed, which is used to guide a stream of sheets in an underlapped formation a sheet transport direction 5. The
25 sheets are guided over the feed table 3 against front lays 7 which, in the exemplary embodiment, can be pivoted about an

axis 9 running transversely with respect to the sheet transport direction 5. The front top lays 7 are disposed one behind another - as viewed transversely with respect to the sheet transport direction 5 - and at a distance from one another. In connection with the present invention, the term "front top lays" is also understood to be front lays.

Provided in the area of the feed table 3 is a non-illustrated side lay, with the aid of which a sheet resting on the front lays 7 can be aligned transversely with respect to the sheet transport direction 5.

Disposed on the front lays 7 are guide rollers 11, which support the sheets on their underside. The sheets, whose leading edge is aligned transversely with respect to the sheet transport direction 5 by the front lays 7, are transported onward at the front lays 7, to a following feed drum 13, by a non-illustrated pregripper.

Disposed above the feed table 3 is the guide apparatus 1, of which only a part is shown in Fig. 1. The guide apparatus 1 contains a crossmember 15 which extends transversely over the feed table 3, and in this exemplary embodiment is configured as a front lay guard 17 and prevents foreign bodies from getting to the front lays 7 or the following part of the machine.

The guide apparatus 1 has a number of guide elements 19, which are disposed one behind another in the lateral direction and at a distance from one another, in such a way that, as viewed
5 in the sheet transport direction 5 - they are disposed to align with one of the front lays 7 in each case. The guide elements 19 in the exemplary embodiment are formed by convex separating rollers, which are in each case mounted by ball bearings on a guide element holder 21. In order that the
10 guide elements 19 can be set to the same distance from the feed table 3 during the assembly of the guide apparatus 1, or in each case to a desired distance from the feed table 3, in each case an eccentric 23 is rotatably mounted in the front lay guard 17 and engages in the associated guide element
15 holder 21. The latter is fixed to the front lay guard 17 by a force fit by a clamping device 25 which can be actuated by hand. Each guide element 19 can therefore be released and set off individually, without any tools, via the clamping device
20 25, that is to say that if it is not needed it can be raised to such an extent and fixed that it does not come into contact with the sheets. When the guide element 19 is set on again, the guide element holder 21 is pressed onto the eccentric 23, and therefore onto the adjusted basic position, by a spring element X.

In the case of severely deformed or very sensitive printing materials, the individual guide elements 19 can be set off without any tools.

- 5 Fig. 2 shows - as viewed in the sheet transport direction 5 - a detail from the guide apparatus 1 according to Fig. 1 in the area of a drive side of the machine. Identical parts are provided with the same reference symbols, so that to this extent reference is made to the description relating to Fig. 1
- 10 1. The front lay guard 17, which has a stable profile, is mounted on the drive and operator side of the machine by bolts 27 such that it can be pivoted about an axis 29 running transversely with respect to the sheet transport direction 5, in each case on a rack 31, of which in Fig. 2 only the rack 31
- 15 disposed on the drive side can be seen. The racks 31 are part of a guide 33, which are used to open the front lay guard 17 and to set the distance of the guide elements 19 from the feed table 3, and can be displaced in the vertical direction here.
- 20 As can be seen in Fig. 3, in each case a lifting device 35 is fitted to the racks 31 such that it can be pivoted about an axis 37 running transversely with respect to the sheet transport direction 5. In this exemplary embodiment, the lifting devices 35 are each formed by a pneumatic cylinder 39,
- 25 which is attached by a hinge in the lower part of the front lay guard 17, close to the guide elements 19.

Mounted on each of the racks 31 is a coupler 43, each of which has a slot 41 and is connected by a hinge to the front lay guard 17. Because of this configuration, the front lay guard 17 with the guide elements 19 disposed on it can be displaced into two defined positions in the sheet transport direction 5. As can be seen from Fig. 3, which shows part of the guide 33 in side view, in a first position of the front lay guard 17, illustrated by a continuous line, the guide elements 19 are disposed at only a very short distance from the front lays 7. The distance between the guide elements 19 and the front lays 7 can be enlarged by the lifting devices 35, which pivot the front lay guard 17 around the axis 29 in such a way that the guide elements 19 are displaced, counter to the sheet transport direction 5, into the position illustrated by a dashed line in Fig. 3. In order that any desired distance can be set between the guide elements 19 and the front lays 7, in an exemplary embodiment which is not illustrated, a motor-adjustable stop is provided instead of the coupler 43.

As can be seen from Fig. 4, which shows part of the guide 33 described with reference to the preceding figures, and from Fig. 2, the racks 31 mesh with a geared shaft 45, which is rotatably mounted in a fixed location in side walls 46 of a machine frame, on the drive side and operator side, and preferably leads through the side wall 46 (Fig. 2) on the

operator side. There, a third rack 44, which runs parallel to the racks 31 and can be seen in Fig. 5, meshes with the geared shaft 45 on the outside.

5 As can be seen from Fig. 4, all three racks 31, 44 are guided by cam rollers 47 and 49, which are disposed on opposite sides of the racks 31, 44 and at a vertical distance from each other. The cam roller 47 is mounted by a bolt 51 fitted to the machine frame (side wall 46, Fig. 2). The other cam
10 roller 49, which is seated on a bolt 53, is pressed resiliently against the racks 31, 44 by a spring element 57, which is formed here by a leaf spring 55, is fitted to a fixed abutment 59 fixed to the frame and acts on the bolt 53, as a result of which the teeth of the racks 31 and those of the
15 third rack 44 are pressed into the teeth of the geared shaft 45. This provides play-free guidance.

In addition, the guide apparatus 1 has a height-adjusting device 61, of which one exemplary embodiment is illustrated in
20 Fig. 5. The height-adjusting device 61 is used to change the distance between the guide elements 19 and the feed table 3. For this purpose, the guide 33 having the guide elements 19 is moved, as will be explained in more detail below.

25 The height-adjusting device 61 contains a first drive 63, which is preferably formed here by a pneumatic piston/cylinder

unit 65, which contains a cylinder 69 fitted to an angle 67 fixed to the frame and a piston rod 71 passing through the cylinder. At a first end 73, the piston rod 71 is fixed to the third rack 44. It can be seen from Fig. 5 that the piston rod 71 is essentially disposed so as to align with the third rack 44.

The height-adjusting device 61 also has a second drive 75, which contains an actuating motor 77 which, via a gearbox 79, drives a gear wheel 83 that is connected so as to rotate with an actuating element 81. The actuating element 81 is formed here by a threaded sleeve 85 which has an external thread and is screwed into a threaded hole in a bearing plate 87 disposed fixed to the frame. When the gear wheel 83 is driven, the threaded sleeve 85 is screwed into or out of the bearing plate 87 - depending on the direction of rotation of the gear wheel 83 - and is therefore displaced vertically upward in the direction of the piston rod 71 or in the opposite direction, that is to say downward. During the displacement of the threaded sleeve 85 in the direction of the piston rod 71 of the first drive 63, the threaded sleeve 85 presses, via a ball-bearing mounted, rotatable bush 89, on a driver 90 that is fitted to the piston rod 71 of the piston/cylinder unit 65, and displaces the piston rod 71 and the third rack 44 upward in the vertical direction. At the same time, the geared shaft 45 in which the third rack 44 engages is rotated. Since the

racks 31 of the guide 33 also engage in the geared shaft 45, the two racks 31, and therefore the entire guide 33, on which the front lay guard 17 with the guide elements 19 is disposed, are displaced to a desired guide-element distance from the

5 feed table 3.

With the aid of the actuating motor 75 and the gearbox 79, the distance between the front lay guard 17 and the feed table 3 can be set very precisely and can readily be set optimally to
10 the respective printing-material thickness and stiffness of the sheets, to the sheet format and to the machine speed.

In order to open the front lay guard 17, that is to say to increase the distance between the guide elements 19 and the
15 feed table 3 considerably, the first drive 63 is activated and the piston rod 71 of the pneumatic piston/cylinder unit 65 is extended completely, is therefore displaced as far as possible in the vertical direction, as a result of which the entire
20 guide 33 with the front lay guard 17 and the guide elements 19 rotatably mounted on the latter are lifted away from the feed table 3. As a result of the displacement of the guide 33 with the aid of the first drive 63, good accessibility to the front
lays 7 and to the feed cylinder 13 can be produced in a straightforward manner. When the piston rod 71 has been
25 extended completely, the driver 90 is disposed at a distance from the bush 89 or is lifted off the bush 89. The connection

between the drives 63 and 75 is therefore uncoupled when the first drive 63 is actuated.

When the guard is opened beyond the operating state (here 5 20 mm) permitted by the safety regulations, the machine is switched off for the purpose of protecting the personnel, although inching continues to be possible.

It remains to be recorded that the first drive 63 is used only 10 for opening the front lay guard 17, and the second drive 75 for the precise setting of the distance between the front lay guard 17 or the guide element 19 from the feed table 3. In addition, it becomes clear that when the first drive 63 is activated, in the exemplary embodiment illustrated in Fig. 5, 15 the drive is automatically uncoupled from the second drive 75. In an advantageous exemplary embodiment, provision is made for the opening of the front lay guard 17, that is to say the action of spacing the guide 33 away from the feed table 3, to also be possible by the second drive 75 of the height- 20 adjusting device 61, that is to say the threaded bush 85 of the latter can be unscrewed from the bearing plate 87 to such an extent that it is possible to take action in the machine in the area of the guide apparatus 1. As a result, in the event of failure of the first drive 63, it is possible to ensure 25 that the guide apparatus 1 can nevertheless still be opened.

The guide apparatus 1 also has a foreign body protective apparatus 91, which serves the purpose of activating one of the drives 63, 75 of the height-adjusting device 61, the first drive 63 in the exemplary embodiment illustrated in Fig. 5, in order to move the guide apparatus 1 away from the feed table 3. The foreign-body protective apparatus 91 has a single limit switch 93 which is disposed underneath the second drive 75 and which senses the position of a switch rod 97 via a sensing lever 95. The switch rod 97 is screwed into a threaded hole 99 of a connecting element 101 which can be displaced only in the threaded sleeve 85 and is formed here by a hexagonal rod. At its end facing away from the switch rod 97, the connecting element 101 is firmly connected to the piston rod 71.

The function of the foreign-body protective apparatus 91 is now described. If, due to the actuating motor 77, the distance of the front lay guard 17 or the guide element 19 disposed on the latter from the feed table 3 is adjusted, the switch rod 97 is rotated into or out of the threaded hole 99 in the connecting element 101. The switch rod 97 is therefore not displaced in the process. When the front lay guard 17 is opened with the aid of the first drive device 63, the piston rod 71 of the piston/cylinder unit 65 moves upward in the vertical direction and, in so doing, takes the connecting element 101 and the switch rod 97 screwed into the latter with

it. As a result, the limit switch 93 is depressed via the sensing lever 95. If, therefore, during continuous operation, a foreign body should get between the front lay guard 17 and the feed table 3 and become jammed in there, as a result of which the guide 33 and therefore also the piston rod 71 were to be lifted in the vertical direction through a preferably only very small distance, then the limit switch 93 would be depressed immediately and the front lay guard 17 would be opened, that is to say the first drive 63 would be activated, so that the guide 33 with the front lay guard 17 disposed on the latter would be moved upward, away from the feed table 3. The limit switch 93 is preferably depressed when the forces acting on the front lay guard 17 are greater than 50 N. When the front lay guard 17 is opened, the machine is preferably switched off.

In an exemplary embodiment of the guide apparatus 1, a non-illustrated adjustable-height brush, for example, is disposed on the front lay guard 17 and reduces the turning up of the trailing edge of the sheet. The trailing edge of the sheet is turned up as a result of the fact that the front lays, as they swing back toward the feed table 3, enter the plane of the sheet and lift the sheet. As a result, thin printing materials in particular are accelerated vertically with respect to the sheet running direction, and a wave which runs through the sheet is produced, as a result of which the end of

the sheet which is running out of the guide elements and becoming free flips up. By pressing down the trailing edge of the sheet, the noise at the feeder of the machine can be reduced.

5

In order to activate the first and second drives 63, 75 and the lifting device 35, in an advantageous exemplary embodiment a switch console is provided at which a machine operator, if required, can adjust the vertical position of the front lay guard 17 or the guide elements 19 with respect to the feed table 3, and also their distance from the front lays 7, manually by pressing a pushbutton. The guide apparatus 1 preferably has no parts that project beyond the feed table 3 in the lateral direction of the machine. As a result, the machine operator can simply remove misfed sheets.

With the aid of the guide apparatus 1 described using the preceding figures, the method mentioned at the beginning can readily be implemented. In a preferred embodiment, this provides that when the printing-material thickness is input, the front lay guard 17 with the guide elements 19 disposed on it is displaced to a short distance, preferably to the shortest distance in the sheet transport direction in relation to the front lays 7 or front top lays for the first sheet of a stream of sheets and, for the second and the following sheets, is displaced - preferably automatically - into the optimum

vertical position and - as viewed in the sheet transport direction - to the optimum distance from the front lays 7. In the case of repeated jobs, the position which it is moved to is preferably exactly the same position of the guide elements

5 19 as in the first print job.

11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044 1045 1046 1047 1048 1049 1050 1051 1052 1053 1054 1055 1056 1057 1058 1059 1060 1061 1062 1063 1064 1065 1066 1067 1068 1069 1070 1071 1072 1073 1074 1075 1076 1077 1078 1079 1080 1081 1082 1083 1084 1085 1086 1087 1088 1089 1090 1091 1092 1093 1094 1095 1096 1097 1098 1099 1100 1101 1102 1103 1104 1105 1106 1107 1108 1109 1110 1111 1112 1113 1114 1115 1116 1117 1118 1119 1120 1121 1122 1123 1124 1125 1126 1127 1128 1129 1130 1131 1132 1133 1134 1135 1136 1137 1138 1139 1140 1141 1142 1143 1144 1145 1146 1147 1148 1149 1150 1151 1152 1153 1154 1155 1156 1157 1158 1159 1160 1161 1162 1163 1164 1165 1166 1167 1168 1169 1170 1171 1172 1173 1174 1175 1176 1177 1178 1179 1180 1181 1182 1183 1184 1185 1186 1187 1188 1189 1190 1191 1192 1193 1194 1195 1196 1197 1198 1199 1200 1201 1202 1203 1204 1205 1206 1207 1208 1209 1210 1211 1212 1213 1214 1215 1216 1217 1218 1219 1220 1221 1222 1223 1224 1225 1226 1227 1228 1229 1230 1231 1232 1233 1234 1235 1236 1237 1238 1239 1240 1241 1242 1243 1244 1245 1246 1247 1248 1249 1250 1251 1252 1253 1254 1255 1256 1257 1258 1259 1260 1261 1262 1263 1264 1265 1266 1267 1268 1269 1270 1271 1272 1273 1274 1275 1276 1277 1278 1279 1280 1281 1282 1283 1284 1285 1286 1287 1288 1289 1290 1291 1292 1293 1294 1295 1296 1297 1298 1299 1300 1301 1302 1303 1304 1305 1306 1307 1308 1309 1310 1311 1312 1313 1314 1315 1316 1317 1318 1319 1320 1321 1322 1323 1324 1325 1326 1327 1328 1329 1330 1331 1332 1333 1334 1335 1336 1337 1338 1339 1340 1341 1342 1343 1344 1345 1346 1347 1348 1349 1350 1351 1352 1353 1354 1355 1356 1357 1358 1359 1360 1361 1362 1363 1364 1365 1366 1367 1368 1369 1370 1371 1372 1373 1374 1375 1376 1377 1378 1379 1380 1381 1382 1383 1384 1385 1386 1387 1388 1389 1390 1391 1392 1393 1394 1395 1396 1397 1398 1399 1400 1401 1402 1403 1404 1405 1406 1407 1408 1409 1410 1411 1412 1413 1414 1415 1416 1417 1418 1419 1420 1421 1422 1423 1424 1425 1426 1427 1428 1429 1430 1431 1432 1433 1434 1435 1436 1437 1438 1439 1440 1441 1442 1443 1444 1445 1446 1447 1448 1449 1450 1451 1452 1453 1454 1455 1456 1457 1458 1459 1460 1461 1462 1463 1464 1465 1466 1467 1468 1469 1470 1471 1472 1473 1474 1475 1476 1477 1478 1479 1480 1481 1482 1483 1484 1485 1486 1487 1488 1489 1490 1491 1492 1493 1494 1495 1496 1497 1498 1499 1500 1501 1502 1503 1504 1505 1506 1507 1508 1509 1510 1511 1512 1513 1514 1515 1516 1517 1518 1519 1520 1521 1522 1523 1524 1525 1526 1527 1528 1529 1530 1531 1532 1533 1534 1535 1536 1537 1538 1539 1540 1541 1542 1543 1544 1545 1546 1547 1548 1549 1550 1551 1552 1553 1554 1555 1556 1557 1558 1559 1560 1561 1562 1563 1564 1565 1566 1567 1568 1569 1570 1571 1572 1573 1574 1575 1576 1577 1578 1579 1580 1581 1582 1583 1584 1585 1586 1587 1588 1589 1590 1591 1592 1593 1594 1595 1596 1597 1598 1599 1600 1601 1602 1603 1604 1605 1606 1607 1608 1609 1610 1611 1612 1613 1614 1615 1616 1617 1618 1619 1620 1621 1622 1623 1624 1625 1626 1627 1628 1629 1630 1631 1632 1633 1634 1635 1636 1637 1638 1639 1640 1641 1642 1643 1644 1645 1646 1647 1648 1649 1650 1651 1652 1653 1654 1655 1656 1657 1658 1659 1660 1661 1662 1663 1664 1665 1666 1667 1668 1669 1670 1671 1672 1673 1674 1675 1676 1677 1678 1679 1680 1681 1682 1683 1684 1685 1686 1687 1688 1689 1690 1691 1692 1693 1694 1695 1696 1697 1698 1699 1700 1701 1702 1703 1704 1705 1706 1707 1708 1709 1710 1711 1712 1713 1714 1715 1716 1717 1718 1719 1720 1721 1722 1723 1724 1725 1726 1727 1728 1729 1730 1731 1732 1733 1734 1735 1736 1737 1738 1739 1740 1741 1742 1743 1744 1745 1746 1747 1748 1749 1750 1751 1752 1753 1754 1755 1756 1757 1758 1759 1760 1761 1762 1763 1764 1765 1766 1767 1768 1769 1770 1771 1772 1773 1774 1775 1776 1777 1778 1779 1780 1781 1782 1783 1784 1785 1786 1787 1788 1789 1790 1791 1792 1793 1794 1795 1796 1797 1798 1799 1800 1801 1802 1803 1804 1805 1806 1807 1808 1809 1810 1811 1812 1813 1814 1815 1816 1817 1818 1819 1820 1821 1822 1823 1824 1825 1826 1827 1828 1829 1830 1831 1832 1833 1834 1835 1836 1837 1838 1839 1840 1841 1842 1843 1844 1845 1846 1847 1848 1849 1850 1851 1852 1853 1854 1855 1856 1857 1858 1859 1860 1861 1862 1863 1864 1865 1866 1867 1868 1869 1870 1871 1872 1873 1874 1875 1876 1877 1878 1879 1880 1881 1882 1883 1884 1885 1886 1887 1888 1889 1890 1891 1892 1893 1894 1895 1896 1897 1898 1899 1900 1901 1902 1903 1904 1905 1906 1907 1908 1909 1910 1911 1912 1913 1914 1915 1916 1917 1918 1919 1920 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666